

FDT5400

Written by Administrator

Monday, 20 June 2011 00:34 - Last Updated Sunday, 21 August 2011 21:29

FDT5400 FIELD MOUNT TRANSMITTER RTD INPUT



FDT5400: 100 ohm Platinum RTD

FDT54x0: reserved for other RTD styles. [Contact](#) factory with your requirements.

- NEMA 4X Splashproof Enclosure
- 3-1/2 Digit Display
- Available for all RTD Types
- Linearizes Platinum RTDs
- 3-Wire Lead Compensation Standard
- Urethane-Coated Circuit Boards
- AC or DC Power Options

[FDT5400](#)

[PDF](#)

[DATA SHEET](#)

FDT5400

Written by Administrator

Monday, 20 June 2011 00:34 - Last Updated Sunday, 21 August 2011 21:29

FDT5400 Series RTD Input Transmitters provide an isolated DC output proportional to temperature as measured by a resistance thermometer (RTD). Model FDT5400 specifically designates 100 ohm platinum RTD input: additional model numbers are reserved for other RTD types.

Standard three-wire input circuitry compensates for lead wire resistance: a 4-wire input option is available. Platinum RTDs are linearized to provide true temperature indication. (Other types may or may not be: [contact us](#) to discuss your specific requirements.) A low-drift input amplifier helps assure accurate readings under varying ambient conditions.

A rugged NEMA 4X splashproof, corrosion-resistant housing protects the transmitter in outdoor and industrial environments. The circuit boards are urethane coated for protection against condensation and contaminants. FDT5400 Series transmitters include a 3-1/2 digit user-rangeable display to provide local process indication in degrees or other engineering units.

Available options include AC and DC power choices and reverse-acting transmitter (decreasing output with increasing input).

For field mount transmitters without a display, select any plug-in transmitter module plus our ENCL-1 NEMA-4X enclosure. (see [Accessories](#) page)

ORDERING INFORMATION

Model Number:

Specify Model FDT5400 [Contact Us](#) with 100 ohm platinum RTD or other RTD inputs. Other model numbers will be assigned up

Display:

If not otherwise specified, the display will be calibrated in degrees per your input range. Other calibration

FDT5400

Written by Administrator

Monday, 20 June 2011 00:34 - Last Updated Sunday, 21 August 2011 21:29

Power:

Add suffix A (for example, FDT5400A) for AC power, D for DC power. Specify 115Vac, 230Vac, 12Vdc or

RTD Type:

Model FDT5400: 100 ohm platinum. Others as determined by assigned model number

Input Range:

Specify any input range allowed by the "Input Capabilities" spec, below.

Output Range:

Specify any DC voltage or current range allowed by the "Output Capabilities" spec, below.

4-Wire RTD Input:

Specify Option 4W.

Reverse-Acting Transmitter (increasing output with increasing input)

Change last digit of the model number to 1 (for example, FDT5401A).

Loop-Powered Output:

4/20mA "current sink" output stage for connection to devices whose inputs provide 24Vdc loop

Urethane Coating:

Specify Option U.

Conduit Opening:

Standard: None. The enclosure has knockouts. Option NPT: Single 1/2 inch NPT fitting (glass-fiber reinforced).

ELECTRICAL CONNECTIONS

Connections are made to 8 terminals within the enclosure:

1: RTD.

2: RTD (same end of RTD as terminal 1). When connecting to 2-wire RTD, jumper terminals 1 and 2. **3:** RTD (opposite end)

4: Standard - no connection. Option 4W - 4th wire of RTD (same end as terminal 3).

5: Output plus.

6: Output minus.

7: Power (AC or, if DC power option, DC plus).

8: Power (AC or, if DC power option, DC minus).

DETAILED SPECIFICATIONS

RTD Type:

Any RTD from 10 to 2,000 ohms. (Model FDT5400 for 100 ohm platinum, other models FDT54x0 for other)

Input Connection:

3-wire connection is standard. Specify Option 4W for 4-wire RTD.

Input Capabilities:

Minimum span 10 deg. C (18 deg. F) or 1 ohm, whichever is greater. Any range up to maximum covered

Voltage Output Capabilities:

1 volt minimum output span, -10 to +15V absolute limit. Offset ranges are allowed. Maximum output load

Current Output Capabilities:

1mA minimum output span, 0 to +25mA absolute limit. Positive offsets are allowed, negative outputs are

FDT5400

Written by Administrator

Monday, 20 June 2011 00:34 - Last Updated Sunday, 21 August 2011 21:29

Display Capabilities:

Low end and full scale readings may be anywhere between -1999 and +1999 counts. A fixed decimal point

Endpoint Accuracy (factory calibration) :

+/-0.1% of span or 0.02 ohms, whichever is greater.

Adjustability:

Zero and span each are adjustable approx. +/-15% of span.

Linearity:

Platinum RTDs are linearized. Copper is inherently linear. Contact factory for information on others.

Response Time:

Under 100 milliseconds.

FDT5400

Written by Administrator

Monday, 20 June 2011 00:34 - Last Updated Sunday, 21 August 2011 21:29

Isolation:

3-way (Power/Input/Output) 1,500Vac rms (2,100V peak).

Guaranteed Operating Temperature:

-10 to +60	°	C (14 to 140	°	F).
------------	---	--------------	---	-----

Temperature Stability:

+/- (0.02% of span plus 0.002	C) per	°	C, or be
-------------------------------	--------	---	----------

Power Requirements:

AC, 115 or 230Vrms, 50/60Hz, 2.5V-A. DC, 12 or 24V, 2.5W.